

METHOD AND SYSTEM FOR SHARING OVER-ALLOCATED BANDWIDTH  
BETWEEN DIFFERENT CLASSES OF SERVICE  
IN A WIRELESS NETWORK

TECHNICAL FIELD OF THE INVENTION

This invention relates in general to the field of wireless communications, and more particularly to a method and system for sharing over-allocated bandwidth  
5 between different classes of service in a wireless network.

062891.0565-070201

BACKGROUND OF THE INVENTION

Wireline and wireless Internet protocol (IP) networks have traditionally supported a best effort delivery of all traffic. To support enhanced services, multiple types, or classes, of services have been established and assigned certain class of service (CoS) parameters that help engineer queues for each service type.

The CoS parameters include delay, jitter, error rates, and throughput. The CoS parameters can be provisioned on a per IP connection or per flow basis through mechanisms such as resource reservation protocol (RSVP) or can be provisioned on aggregate flows which are classified into service classes. Internet service providers (ISPs) can utilize the service classes, their associated CoS behavior and CoS provisioning to provide tiered service offerings to their business and consumer customers.

Typically, each service class is allocated a bandwidth to transport corresponding traffic in accordance with the CoS policy. The allocation of bandwidth prevents starvation traffic flows at each CoS level. Traffic in excess of the allocated bandwidths for a service class is held, or dropped causing delay and/or retransmissions.

SUMMARY OF THE INVENTION

The present invention provides a method and system for sharing over-allocated bandwidth between different classes of service in a wireless network that subsequently reduce or eliminate problems and disadvantages with previous systems and methods. In a particular embodiment, the present invention uses excess bandwidth from one or more service classes to satisfy excess demand in other service classes.

10 In accordance with one embodiment of the present invention, a method for sharing over-allocated bandwidth between service classes in a wireless network includes transmitting traffic for a first service class in excess of bandwidth allocated to the first service class using  
15 unused bandwidth allocated to a second class. After transmitting traffic for a first service class in excess of bandwidth allocated to the first service class using unused bandwidth allocated to a second class, traffic for a third service class is transmitted in unused bandwidth  
20 remaining in the second service class.

Technical advantages of one or more embodiments of the present invention include more efficient use of the bandwidth available in a wireless sector by sharing over-allocated bandwidth between different classes of service.  
25 Other advantages may include fewer packet and/or call drops and thus reduced retransmissions. Additionally, call capacity of the network is increased while preventing class starvation by allocating bandwidth to each class and using over-allocated bandwidth for excess  
30 traffic in other classes.

00000553-070201

Other technical advantages of the present invention will be readily apparent to one skilled in the art from the following figures, description, and claims.

09898558 "070201

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and its advantages, reference is now made to the following description, taken in conjunction with the accompanying drawings, in which:

FIGURE 1 is a block diagram illustrating a communications network in accordance with one embodiment of the present invention;

FIGURE 2 is a diagram illustrating allocation of bandwidths in a wireless sector of FIGURE 1 in accordance with one embodiment of the present invention; and

FIGURE 3 is a flow diagram a method for sharing over-allocated bandwidth between different classes of service in a wireless sector in accordance with one embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIGURE 1, the communications system 10 includes a wireless network 12 connected to a wireline network 14 through a gateway 16.

5       The wireless network 12 includes a number of base stations (BTSS) 30 connected to base station controllers (BSCs) 32. The BTSS 30 each cover a geographic region or cell or sector 34 of the wireless network 12 and communicate with mobile devices 36 in the cell 34. The  
10       mobile devices 36 may be cell phones, data phones, portable data devices, portable computers, handheld devices, handsets, portable network appliances or other suitable devices capable of communicating information over a wireless link 38.

15       The BSCs 32 are connected to each other in some way, to the Gateway 16 and to a mobile switching center (MSC) 40. The BSCs 32 and the MSC 40 cooperate to provide switch and handoff functionality for the wireless network 12. In this way, voice, video, data and other  
20       information is routed to and from the mobile devices 36 and connections are maintained with the mobile devices 36 as they move throughout, or roam the wireless network 12.

      Wireless link 38 is a radio frequency (RF) link. The wireless link 38 may be based on established  
25       technologies or standards such as IS-54 (TDMA), IS-95 (CDMA), GSM and AMPS, 802.11 based WLAN, or more recent technology such as CDMA 2000 and W-CDMA or proprietary radio interfaces. In a particular embodiment, wireless link 38 comprises a code division multiple access (CDMA)  
30       link based on a CDMA standard and in which packets are

0399550-070204

segmented into radio frames for transmission over the wireless interface and reassembled by the receiving device to reconstitute the packets.

The wireline network 14 includes a packet or other  
5 suitable data network 50 connecting a number of servers  
52 to each other and to the gateway. The packet network  
50 also connects the gateway, and thus the wireless  
network 12 to the public switched telephone network  
(PSTN). Accordingly, mobile devices 36 may communicate  
10 through wireless network 12, packet network 50 and PSTN  
54 with standard telephones, clients and computers using  
modems or digital subscriber line (DSL) connections or  
other telephony devices 58.

The data network 50 may be the Internet, intranet,  
15 extranet, or other suitable local or wide area network  
capable of communicating information between remote  
endpoints. For the Internet embodiment, information is  
transmitted in Internet protocol (IP) packets. It will  
be understood that information may be transmitted in  
20 other suitable packets, including asynchronous transport  
mode (ATM) and other cells or datagrams.

The servers 52 may comprise voicemail servers (VMS),  
fax/modem servers, short message center (SMSC) servers,  
conferencing facilities, authentication, authorization,  
25 and accounting (AAA) servers, billing servers, home  
location registers (HLR), home subscriber servers (HSS),  
domain name servers (DNS) and other suitable servers and  
functionality providing services to mobile devices 36  
and/or to wireless and/or wireline connections in the  
30 communications system 10.

00000553 070201

Referring to FIGURE 2, the horizontal axes of the graphs represent the passage of time. Bandwidth is represented by the vertical axes. In a particular



embodiment, a bandwidth may be allocated to a best effort (BE) class of service 70, assured forwarding (AF) classes of service 72-78, and an expedited forwarding (EF) class of service 80. It will be understood that the allocated  
5 bandwidths may comprise fewer, more, and/or different service classes. For example, the allocated bandwidths may comprise a class having a substantial guarantee of traffic arrival, a class with a limited such guarantee, and a class with no or substantially no such guarantee.

10 In a particular embodiment, the allocated bandwidth are constant or substantially constant. In other embodiments, the allocated bandwidths may vary and may be dynamically determined based on real-time operating character of 12. In either embodiment, the allocated  
15 bandwidth may be based on the priority and/or rate of the corresponding traffic and the current, estimated and/or anticipated traffic volume in the service class. Another portion of the total available bandwidth may be allocated to non-bursty traffic flows that are each substantially  
20 constant in bandwidth usage 82. The non-bursty traffic may include, for example, voice, video, and other real-time traffic connections.

At any given time, the amount of traffic for certain classes of service may consume more or less than the  
25 total amount of allocated bandwidth. Thus, bandwidths may be over-allocated for one or more service classes while under allocated for one or more remaining service classes. This excess traffic 84 or excess bandwidth 86, respectively, may vary with time. For example, at time  
30 t1, excess bandwidth is found in the EF, AF<sub>2</sub>, AF<sub>1</sub>, and

09090558 070204

voice allocated bandwidths while AF<sub>4</sub>, and AF<sub>3</sub> allocated bandwidths have excess traffic. At time t<sub>2</sub>, in contrast, EF, AF<sub>4</sub>, AF<sub>3</sub>, AF<sub>2</sub>, and BE allocated bandwidths have excess bandwidth, while there is excess traffic in AF<sub>1</sub> allocated  
5 bandwidth.

FIGURE 3 shows a method for sharing over-allocated bandwidths between different classes of service in a wireless network in accordance with one embodiment of the present invention. In this embodiment, voice traffic is  
10 considered as well as three classes of service for bursty traffic: EF, AF, and BE. If there is excess traffic, that traffic is transmitted using excess bandwidth in the following order: AF, BE, and then EF. Excess voice bandwidth is used first, and then excess bandwidth for  
15 the other classes in order of increasing priority: BE, AF, and EF. In this particular embodiment, excess bandwidth is first used from non-bursty service classes and then from bursty classes based on priority. This provides maximum remaining bandwidth for the bursty  
20 classes. In this embodiment, excess traffic for lower priority classes is placed in excess bandwidth of higher priority, bursty classes. In other embodiments, excess lower-priority traffic may not be transmitted in over-allocated higher-priority class bandwidths.

Referring now to FIGURE 3, and in accordance with an embodiment of the present invention, the method begins with step 100 wherein the scheduler 17 in the gateway 16 transmits packet traffic in each class using allocated bandwidth. At determination step 102, the scheduler 17  
30 determines whether there is excess of assured forwarding

09898558.070201

09898553-070201

(AF) traffic. If there is excess AF traffic, the Yes branch leads to determination step 108. At determination step 108, the scheduler 17 determines whether there is an excess amount of voice bandwidth. If there is an excess  
5 of voice bandwidth, then, at step 110, excess AF traffic is transmitted using the excess voice bandwidth. At determination step 132, if there is no remaining excess AF traffic, then the scheduler 17 moves on to determination step 104 to determine whether there is  
10 excess traffic in the next highest priority service class in which in the illustrated embodiment is BE.

Returning to determination step 132, if there is remaining excess AF traffic after the excess voice bandwidth is fully used, then the Yes branch of  
15 determination step 132 leads to determination step 112. The No branch of determination step 108 also leads to determination step 112. At step 112, if there is excess BE bandwidth, the excess AF traffic is transmitted in the excess BE bandwidth at step 114. At determination step  
20 134, if there is no remaining excess AF traffic, then the scheduler moves on to determination step 104 to determine whether there is excess BE traffic.

Returning to determination step 134, if there is remaining excess AF traffic after the excess BE bandwidth  
25 is fully used, then the Yes branch leads to determination step 116. The No branch of step 112 also leads to determination step 116. At step 116, if there is not excess EF allocated bandwidth, then all excess bandwidth from one, more or all usable service classes has been  
30 fully used and the scheduler 17 has reached the end of

Returning to determination step 138, if there is  
25 remaining excess BE traffic after the excess voice  
bandwidth is fully used, then the Yes branch of  
determination step 138 leads to determination step 124.  
The No branch of determination step 120 also leads to  
determination step 124. At step 124, if there is excess  
30 AF bandwidth, the excess BE traffic is transmitted in the

At determination step 106, the scheduler 17 determines whether there is excess expedited forwarding (EF) traffic. If there is excess EF traffic, the Yes branch leads to determination step 128. At determination step 128, the scheduler 17 determines whether there is an excess amount of voice bandwidth. If there is an excess of voice bandwidth, then, at step 130, excess EF traffic is transmitted using the excess voice bandwidth. At

determination step 148, if there is no remaining excess EF traffic, then the scheduler 17 has reached the end of the process.

Returning to determination step 148, if there is  
5 remaining excess EF traffic after the excess voice  
bandwidth is fully used, then the Yes branch of  
determination step 148 leads to determination step 150.  
The No branch of determination step 128 also leads to  
determination step 150. At step 150, if there is excess  
10 BE bandwidth, the excess EF traffic is transmitted in the  
excess BE bandwidth at step 152. At determination step  
154, if there is no remaining excess EF traffic, then the  
scheduler has reached the end of the process.

Returning to determination step 154, if there is  
15 remaining excess EF traffic after the excess BE bandwidth  
is fully used, then the Yes branch leads to determination  
step 156. The No branch of step 150 also leads to  
determination step 156. At step 156, if there is not  
excess AF allocated bandwidth, then all excess bandwidth  
20 from one, more or all usable service classes has been  
fully used and the scheduler 17 has reached the end of  
the process. If at step 156 there is excess AF  
bandwidth, the excess EF traffic is transmitted in the  
excess AF bandwidth at step 158. At this point all  
25 available excess bandwidth has been used and the  
scheduler has reached the end point of the process.

Although the present invention has been described  
with several embodiments, a myriad of changes,  
variations, alterations, transformations, and  
30 modifications may be suggested to one skilled in the art,

0969559.070201

and it is intended that the present invention encompass such changes, variations, alterations, transformations, and modifications as fall within the scope of the appended claims.

062891.0565